

AIR VALVES

Model : WB - EAV EXHAUST AIR VALVE

Model : WB - SAV SUPPLY AIR VALVE





INTRODUCTION

Model WB-EAV & SAV are used for the supply and exhaust of cooled and heated air in small areas such as toilets & vessel rooms with ceiling to floor height up to 2.4m . The diffuser can be installed in both ceiling or exposed duct installations. Diffuser is constructed of aluminum in standard white epoxy powder coating.

Mounting ring makes installation a breeze, just screw on!

Model : WB - EAV EXHAUST AIR VALVE





mounting bracket

DIMENSIONAL DETAILS

QUICK SELECTION CHART

| Size | Duct size | Face | Blade | Height | CMH Range | NC |
|------|-----------|------|-------|--------|-----------|-----|
| 100 | 97.5 | 138 | 75 | 40 | 50-90 | <36 |
| 125 | 122.5 | 164 | 99 | 46 | 75-130 | <36 |
| 150 | 147.5 | 202 | 119 | 50 | 100-170 | <36 |
| 200 | 197.5 | 248 | 157 | 63 | 125-220 | <36 |

Model : WB - SAV SUPPLY AIR VALVE



mounting bracket

DIMENSIONAL DETAILS

QUICK SELECTION CHART

| Size | Duct size | Face | Blade | Height | CMH Range | NC |
|------|-----------|------|-------|--------|-----------|-----|
| 100 | 97.5 | 138 | 92 | 40 | 50-90 | <36 |
| 125 | 122.5 | 164 | 111 | 46 | 75-130 | <36 |
| 150 | 147.5 | 202 | 135 | 50 | 100-170 | <36 |
| 200 | 197.5 | 248 | 194 | 63 | 125-220 | <36 |